

[19/Dec/2018 Updated PassLeader Free 300-115 Study Guide with 971q Questions and Answers

New Updated 300-115 Exam Questions from PassLeader 300-115 PDF dumps! Welcome to download the newest PassLeader 300-115 VCE dumps: <https://www.passleader.com/300-115.html> (971 Q&As) Keywords: 300-115 exam dumps, 300-115 exam questions, 300-115 VCE dumps, 300-115 PDF dumps, 300-115 practice tests, 300-115 study guide, 300-115 braindumps, Implementing Cisco IP Switched Networks Exam P.S. New 300-115 SWITCH dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpV1dGa2Q3czNVNG8 >> New 300-101 ROUTE dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpZEE0S2YxR3ZMUWs >> New 300-135 TSHOOT dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpSV82OWY1cnV1Z3c NEW QUESTION 947 Which two statements about normal-range VLANs are true? (Choose two.) A. You can delete VLANs 1002 through 1005 in transparent mode only. B. The vlan.dat file is stored in RAM and copied to the NVRAM when you save the configuration. C. Configurations are saved in the vlan.dat file. D. You can add, modify, and remove configurations in VTP server mode and VTP client mode. E. You can add VLANs in VTP server mode. Answer: CE NEW QUESTION 948 Which three statements about extended VLANs are true? (Choose three.) A. The lowest extended VLAN number is 1006. B. The lowest extended VLAN number is 1002. C. Any VLAN ID can be used as an extended VLAN. D. They are recognized only by VTP version 3. E. They are propagated by VTP by default. F. They require the extended system ID to be enabled on the device. Answer: ADF NEW QUESTION 949 Which command must be configured on the physical ports of a Layer 3 EtherChannel? A. ip address <subnet mask> B. switchport trunk encapsulation dot1q C. no switchport D. switchport mode access Answer: C NEW QUESTION 950 Which feature can you enable on your network to most effectively limit unknown traffic? A. DHCP packet rate limiting B. unicast storm control C. multicast storm control D. broadcast storm control E. ARP packet rate limiting Answer: B NEW QUESTION 951 Which two statements about native VLANs are true? (Choose two.) A. All outgoing traffic without a VLAN tag is tagged with the native VLAN. B. All untagged traffic that arrives on the device is placed into the native VLAN. C. The VLAN tag is stripped from all incoming traffic that matches the native VLAN. D. They are propagated through VTP. E. The default native VLAN is VLAN 11. F. All incoming traffic that matches the native VLAN is dropped at the switch. Answer: BD NEW QUESTION 952 Which two TLVs are mandatory in LLDP advertisements? (Choose two.) A. Platform TLV B. System Capability TLV C. Network Policy TLV D. System Name TLV E. Native VLAN TLV Answer: BD NEW QUESTION 953 Which statement about the connection of two switches with several links using LACP link aggregation on IOS is true? A. By default, when an LACP channel is configured, the LACP channel mode is off. B. By default, when an LACP channel is configured, the LACP channel mode is on. C. By default, when an LACP channel is configured, the LACP channel mode is active. D. By default, when an LACP channel is configured, the LACP channel mode is passive. Answer: B NEW QUESTION 954 Which two statements about configuring a voice VLAN on a switch port are true? (Choose two.) A. The port must be operating in untrusted mode. B. Tagged traffic is not supported. C. It must be configured separately from the VLAN that carries data traffic. D. If the port is trusted, data traffic that passes through the Cisco IP Phone maintains its QoS values. E. The port must be operating in trusted mode. F. Cisco Discovery Protocol must be disabled on the switch port. Answer: CD NEW QUESTION 955 Which statement about SPAN functionality for an EtherChannel group is true? A. It can be configured as a SPAN source or a SPAN destination port. B. It can be configured as a SPAN source but not as a SPAN destination port. C. It can be configured as a SPAN destination but not as a SPAN source port. D. It cannot be configured as a SPAN source or a SPAN destination port. Answer: B NEW QUESTION 956 How does the Spanning Tree Protocol determine path cost? A. interface hop count B. interface reliability C. interface bandwidth D. interface load E. interface delay Answer: C NEW QUESTION 957 Drag and Drop

It supports authentication.

HSRPv1 and HSRPv2 use the same packet format.

It can share a virtual MAC or IP address among a group of routers.

It is a Cisco-proprietary implementation of FHRP.

It is supported on Layer 3 interfaces, including tunneled interfaces.

HSRPv1 and HSRPv2 use different multicast addresses for hello packets.

The HSRPv2 group numbers ranges from 0 to 255.

True

www.passleader.com

Answer:

HSRPv1 and HSRPv2 use the same packet format.

It is supported on Layer 3 interfaces, including tunneled interfaces.

The HSRPv2 group numbers ranges from 0 to 255.

True

HSRPv1 and HSRPv2 use different multicast addresses for hello packets.

It can share a virtual MAC or IP address among a group of routers.

It is a Cisco-proprietary implementation of FHRP.

It supports authentication.

www.passleader.com

NEW QUESTION 958 If EtherChannel guard is configured on a device, which result happens when the device detects a misconfiguration on a connected device? A. Spanning tree is disabled for the VLANs associated with the EtherChannel. B. The port generates a syslog message. C. The EtherChannel configuration is removed from the running configuration of the device. D. The port is error disabled. Answer: D

NEW QUESTION 959 Which two options are benefits of using VSS for chassis virtualization? (Choose two.) A. It supports GLBP to balance VSS traffic. B. It provides multiple points of management for redundancy and improved support. C. It uses a single database to manage configuration for multiple switches. D. It provides a single point of management for improved efficiency. E. It requires only one gateway per VLAN. Answer: DE

NEW QUESTION 960 What happens if an interface within channel group is configured as SPAN destination? A. Portchannel will forward traffic to source SPAN. B. It will not be operational. C. The link will be in error-disabled. D. The interface will be removed from the channel group. Answer: D

NEW QUESTION 961 Which feature is new in RPVST+? A. BackboneFast is implemented. B. UplinkFast is implemented. C. Only the root bridge sends configuration BPDUs. D. All ports can generate and send BPDUs. Answer: D

NEW QUESTION 962 Download the newest PassLeader 300-115 dumps from passleader.com now! 100% Pass Guarantee! 300-115 PDF dumps & 300-115 VCE dumps: <https://www.passleader.com/300-115.html> (971 Q&As) (New Questions Are 100% Available and Wrong Answers Have Been Corrected! Free VCE simulator!) P.S. New 300-115 SWITCH dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpV1dGa2Q3czNVNG8 >> New 300-101 ROUTE dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpZEE0S2YxR3ZMUWs >> New 300-135 TSHOOT dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpSV82OWY1cnVIZ3c